

规格型号	容量 (L)	外形尺寸 (左右×前后×高)
B-R-J-1-130/1.75/0.7	130	1380×1685×1770
B-R-J-1-140/1.90/0.7	140	1450×1685×1770
B-R-J-1-150/2.00/0.7	150	1530×1685×1770
B-R-J-1-160/2.15/0.7	160	1610×1685×1770
Q-B-J-2-140/1.86/0.6-2.0	140	
Q-B-J-2-150/2.00/0.6-2.0	150	
Q-B-J-2-160/2.15/0.6-2.0	160	
Q-B-J-2-180/2.42/0.6-2.0	180	
Q-B-J-2-200/2.69/0.6-2.0	200	
Q-B-J-2-240/3.25/0.6-2.0	240	

集热面积 (m <sup>2</sup> )	额定压力 (MPa)	额定电压 (V) 频率 (Hz)	额定功率 (KW)	内胆材质/厚度
1.75	0.7	AC220/50	2/1.5	搪瓷钢板/1.8
1.9	0.7	AC220/50	2/1.5	搪瓷钢板/1.8
2	0.7	AC220/50	2/1.5	搪瓷钢板/1.8
2.15	0.7	AC220/50	2/1.5	搪瓷钢板/1.8
1.86	0.6	AC220/50	2/1.5	SUS316L/1.0
2	0.6	AC220/50	2/1.5	SUS316L/1.0
2.15	0.6	AC220/50	2/1.5	SUS316L/1.0
2.42	0.6	AC220/50	2	SUS316L/1.2
2.69	0.6	AC220/50	2	SUS316L/1.2
3.25	0.6	AC220/50	2	SUS316L/1.2

真空管长度(m)

/支数

1.8/13

1.8/14

1.8/15

1.8/16

1.8/14

1.8/15

1.8/16

1.8/18

1.8/20

1.8/24

蓝色部分建议不放